

WOVENFLOORING



























BY DICKSON

TECHNICAL INFORMATION

CLEANGARD®
INTEGRATED PROTECTION
by DICKSON

FRAYGUARD®
CLEAN CUT
by DICKSON

SOUNDGUARD®
ACOUSTIC INSULATION
by DICKSON

| | STANDARD | ALLURE, BOREAL, ECUME, ELEGANCE, MIRAGE |
|-------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
|  Use classification | EN ISO 10874 ASTM D 5252 | 33 Heavy Commercial 5/5 |
|  Fire classification | EN 13501-1 ASTM E 648 ASTM D2859 | Cfl s1 1st Class Methamine Pill Test - CSPC FF1-70: pass |
|  Optical smoke density | ASTM E 662 | < 450 |
|  Soundproofing | ISO 10140-3 ASTM E 492 | 18 dB IIC 59 |
|  Sound absorption coefficient α_w | EN ISO 354 | 0,05 |
|  Roll width | EN 426 | 200 cm |
|  Roll length | EN ISO 24341 | 25 m |
|  Tile packaging and size | EN ISO 24342 | 50 x 50 cm Box of 16 tiles (4 m ²) |
|  Thickness* (+/- 0,3 mm) | ISO 1765 | 4 mm |
|  Weight | ISO 8543 | 3,55 kg/m ² |
|  Natural distortion** | | Maximum 2% |
|  Castor chair | EN 985-A | Intensive use |
|  Body voltage | ISO 6356 | < 2,0 kv |
|  Residual indentation | EN ISO 24343-1 ASTM F 914 | < 0,2 mm 0,18 mm |
|  Static load | ASTM F970 | Conform 250 Psi |
|  Compression recovery | | 95% |
|  Fraying | EN ISO 10833 | Frayproof |
|  Thermal resistance | ISO 8302 | Suitable for underfloor heating |
|  Dimensional stability | ISO 2551 | < 0,1% |
|  Colour fastness to light | ISO 105 B02 AATCC 16 E | 8/8 5/5 |
|  Colour fastness to weather | ISO 105 B04 | 5/5 |
|  Slip resistance dry (dynamic coefficient of friction) | EN 13893 ASTM C 1028 | $\mu > 0,30$ 0,81 |
|  Slip resistance wet (ramp test with oil) | DIN 51130 ASTM C 1028 | R9 0,61 |
|  CE Certification | EN 14 041 | 0493-CPD-0101 |
|  Floorscore Certification (rolls + tiles) | SCS-EC10.2-2007 | SCS - FS - 02719 |
|  LEED® | This product can help you earn points within the framework of Leed version 4 and meet the requirements regarding indoor environmental quality: low-emitting materials | |

According to EN 1307 standard

* All our ranges can be combined together for your projects. A slight difference in thickness, due to the different structures of the woven side, is possible and cannot exceed 0.6 mm.

** Dickson flooring is a textile product, composed on the surface of warp threads aligned and associated with weft threads, by the weaving technique. The perfect perpendicularity of the warp and weft threads does not exist. Therefore, woven vinyl floors will always present natural warp and/or weft deformations that will accentuate the authentic appearance of the weave. Recognizing that this natural phenomenon can alter the final aesthetic result beyond a certain limit, Dickson has set a tolerance for all of its woven flooring lines. Weft deformation: Dickson Flooring tolerance limit = 2%. Visual aspect: our Dickson flooring is composed of a weave of PVC-coated polyester monofilaments combined with an acoustic and technical undercoat by heat-setting and coating. The action of heat, at the heart of our production process, allows the different elements of our products to melt together, thus ensuring their resistance to wear and tear and perfect dimensional stability. Thus, the discrete amalgam of polymers can be detected on the wear side without altering the quality of our products in any way. In addition, the woven structure adds character to the look of your flooring and naturally plays with the light. Varying with the shape, colour and layout pattern, the deep and subtle hues of your flooring change according to the lighting and perspective.

BluSky Products Pty Ltd ABN 71 616 950 371

A: 9 Venture Close Morisset NSW 2264 P: +61 2 98320848 F: +61 2 98320843 E: info@bluskyproducts.com.au

www.bluskyproducts.com.au