

# Softpile

Beige, Coal, Charcoal and Black

## *Product Specification Sheet*

| PROPERTY                               | SPECIFICATION                           | TEST METHOD                   |
|----------------------------------------|-----------------------------------------|-------------------------------|
| <b>Construction</b>                    | 100% ecofi® Polyester Nonwoven Material | <b>N/A</b>                    |
| <b>Weight</b>                          | 389.92gsm +/- 50.86gsm                  | <b>FTM NW503 (ASTM D3776)</b> |
| <b>Width</b>                           | 2.03m                                   | <b>FTM NW502 (ASTM D3774)</b> |
| <b>Thickness</b>                       | 6.10mm +/- 0.64mm                       | <b>FTM NW504 (ASTM D5729)</b> |
| <b>Tensile Strength</b>                | MD 45.36kg min<br>CMD 58.97kg min       | <b>FTM NW505 (ASTM D5034)</b> |
| <b>Elongation at 11.34kg (Instron)</b> | MD 70% +/- 20%<br>CMD 50% +/-           | <b>FTM NW506 (ASTM D5034)</b> |
| <b>Pile Height</b>                     | 3.0mm +/- 0.5mm                         | <b>FTM NW523</b>              |
| <b>Appearance</b>                      | Match Approved Standard                 | <b>Visual</b>                 |
| <b>Colours</b>                         | Beige, Coal, Charcoal and Black         | <b>Visual</b>                 |