

# Product Data Sheet

## SABA Activator 9707



**Description** SABA Activator 9707 is an CMR-free promoter (1-component).

**Areas of application** SABA Activator 9707 is suitable for use as a promoter for cleaning and pre-treating various non-porous substrates such as metals, plastics, coatings and lacquers in conjunction with for instance SABA MS Polymer products.

- Advantages**
- does not contain isocyanates or CMR substances
  - short evaporation time
  - single-action cleaning and activation (in the case of light soiling)

### Technical data

Properties*	
Base	titanate
Viscosity at 23 °C (EN 12092)	≈ 10 mPa.s
Density (EN ISO 2811-2)	≈ 800 kg/m <sup>3</sup>
Solids content	≈ 1%
Application temperature (min./max.)	+5 °C / +35 °C
Substrate temperature (min./max.)	+5 °C / +35 °C, +3 °C above the dew point
Drying time (minimum)	≈ 10 minutes
Open time (maximum)	≈ 3 hours
Coverage	≈ 100 g/m <sup>2</sup>
Colours (standard)	transparent
Packaging	1-litre canister (packaging contains 12 units)
Shelf life	12 months in unopened original packaging, if protected against moisture and direct sunlight. Limited shelf life after opening.
Storage temperature (min./max.)	+5 °C / +25 °C

\* Tested according to SABA Analysis Method unless stated otherwise.

**Equipment** Clean, dry, lint-free cloth.

**Application**

**Bonding surface preparation:** Bonding surfaces must be dimensionally stable, dry, homogenous and free of grease, oil, dust or loose parts.

**Application:** Apply the promoter in a single, thin, unidirectional, even layer. We recommend making a note on the packaging of the date it was first opened and pouring the amount you need into a small jar. After doing so, immediately reseal the packaging. Do not pour residual material back into the packaging.

**Curing mechanism:** The drying time depends on humidity and temperature.

**Safety recommendations** It is very important to BluSky that our products are used safely and handled responsibly. For more safety information, please refer to the relevant SABA material safety data sheet.

**Important** Check compatibility before use or consult BluSky. Once the packaging has been opened, the product has a limited shelf life, therefore the product should be used up as soon as possible. If the product becomes discoloured, cloudy or thickened, it can no longer be used.

**Contact** Our customer service department would be pleased to answer any questions you may have. Please contact your local BluSky office.



BluSky Products Pty Ltd	T: +61 2 9832 0848
	E: sales@bluskyproducts.com.au
www.bluskyproducts.com.au	A: 9 Venture Close. Morisset, NSW 2264

**SABA Dinxperlo BV**  
 Industriestraat 3 NL-7091 DC Dinxperlo • PO Box 3 NL-7090 AA Dinxperlo  
 T +31 (0)315 65 89 99 • F +31 (0)315 65 32 07 • Trade register Arnhem 09065419 • info@saba-adhesives.com • [www.saba-adhesives.com](http://www.saba-adhesives.com)

Our recommendations and instructions for use are based on current knowledge and technology. Customers and users must make their own assessment of our products with regard to their desired utilization and requirements. We are not liable if our products are not used according to our recommendations and/or instructions for use. Our general terms and conditions apply to all requests, instructions for use, quotations, orders, and agreements. These general terms and conditions have been filed with the Arnhem Chamber of Commerce under number 09065419 and can also be consulted on our website at [www.saba-adhesives.com](http://www.saba-adhesives.com). At your request, a copy of these terms and conditions will be sent to you free of charge. The general terms and conditions incorporate a limitation of SABA Dinxperlo BV's liability, as well as the choice of Dutch law as the applicable law and choice of the courts of the Netherlands as the forum. Any disputes ensuing from or relating to requests, instructions for use, quotations, orders, and agreements of SABA Dinxperlo BV must be brought before the competent court in the district where SABA Dinxperlo BV is based.  
 Version number 2021/01/19, this supersedes all previous versions